

TriggAIR Fiber Blowing Machine

FOR CABLE 0.8 - 3mm / DUCT 3, 5, 7, AND 8mm

The TriggAIR is a robust handheld fiber blowing unit optimized for FTTx installation of blown fiber (EPFU) and micro/nano cables. It is battery powered and fits cables 0.8 - 3mm and ducts 3, 5, 7, and 8mm. TriggAIR secures the fiber cable with a mechanical clutch and features an adjustable clamping force. TriggAIR includes a strong transport case, along with batteries, a battery charger, and an assortment of cable seals.



FEATURES

- Battery operated
- Secures fiber by mechanical clutch
- Adjustable clamping force
- Forward and reverse functionality
- Drive wheel with rubber rings ensure a good and soft grip
- Digital display showing speed and distance
- Speed control with constant speed support



INCLUDES

- 110/230 Charger for 12V battery
- 4Ah Milwaukee connector
- 12V lithium battery
- Cable seal assortment:
 - 1.2mm / 0.05" (10 pcs)
 - 1.8mm / 0.07" (10 pcs)
 - 2.2mm / 0.09" (10 pcs)
 - 2.8mm / 0.11" (10 pcs)
- Jetting duct cutter
- User manual



SPECIFICATIONS	
BATTERY	12V, 4Ah Milwaukee
MAX PRESSURE	16 Bar
MAX SPEED	150m/min or 492ft/min
PUSHING FORCE	Up to 30N
CABLE DIAMETER	0.8 - 3mm / 0.03 - 0.12"
DUCT DIAMETER	3, 5, 7, and 8mm / 0.12, 0.20, 0.28, and 0.31"
NET WEIGHT	Approx 2kg / 4.41lbs
AIR CONNECTION	Std. 1/4" CEJN
WxHxD	460 x 370 x 180mm / 18.11 x 14.57 x 7.09" (with case)